

CONSTRUCTION TIPPING TRAILERS

TRANS-KTP: FROM 9 TO 34 T











TRANS-KTP HARDOX 450 CONSTRUCTION TIPPING TRAILERS

















EQUIPMENT OF YOUR CHOICE



Wide choice of eyelets

(A) Bolted Ø 50 mm swivel eye
(B) Bolted Ø 80 mm ball-joint towing eye
(C) Integrated Ø 80 mm ball-joint towing eye
(D) Bolted Ø 50 mm fixed eye
(E) Bolted Ø 50 mm swivel eye
(F) Bolted Ø 40 mm fixed eye



drawbar.





Chassis (width: 900 mm on Trans-KTP 9/11/15/17/22/27 and 700 mm on 24/31/34) allowing the fitting of wide wheels while complying with the regulations and optimising sturdiness and the empty weight.



Complete connections (lighting, braking and tipping system of a second trailer) with swivel rear hitch.



Automatic rear hitch



Central grain chute

- 260 x 175 mm (Trans-KTP 9/11/15)
 - 500 x 300 mm (Trans-KTP 17)
- 500 x 500 mm (Trans-KTP 22/24/27/31/34)


Cover with hydraulic winding (Cabriolet type)












- A 250 or 500 mm aluminium extensions, stackable up to 1 m.
- **B** 70 x 70 mm PVC protections (incompatible with some configurations): upper body edge protection (2 side walls + rear door).
- © 150 or 250 mm pointed high tensile steel extensions* to prevent material build-up and protect the upper body edge.
 - *Welded on models 15/17/22/27, bolted on 24/31/34. Only available with 1-part door on models 15 to 34.

Optimised Tipping and Unloading



Up to 61° tipping system with telescopic cylinder on a double oscillating frame (A) placed in an advanced position in the chassis.

3 First 2 cylinder parts nitrided.





Tapered body fully made of HARDOX 450, for easier unloading of material.





HARDOX 450

TRANS-KTP 17/22/24/27/31/34

The "LARGE-VOLUME" models in the JOSKIN range of heavy-duty tipping trailers










Seal for 1-part door



Hydraulic rear bumper retracting automatically before the door opens



Free-steering axle with manual locking above 15 km/h and when reversing.



1 or 2 self-steering axle(s) effective when driving forward or reversing at all speeds.



Hydro-Pendul suspension (Trans-KTP 24 (2 axles), 31 and 34 (3 axles)) + manual slope position adjustment (A) + automatic height-adjustment (B).



Hydro-Tridem suspension (Trans-KTP 27) with 1,550 mm wheelbase.



Heavy duty, tubular rocker beam.



CONSTRUCTION TIPPING TREASON OFF-SEASON

TRANS-KTP 9/11/15/17

Small, VERSATILE, Sturdy and Compact Tipping Trailers

The JOSKIN Trans-KTP 9/11/15/17 tipping trailers are designed for all types of site work, both for moving your equipment and for on-site operations.



HARDOX 450



1- or 2-part hydraulic rear door with wide opening angle



2-part hydraulic door: manual opening of the 2 parts and hydraulic opening of the high-clearance door + pre-equipment for loading ramps





Roll-Over bogie suspension (Trans-KTP 11 and 15) with parabolic leaves.



Models 9/11/15: tipping system via P.T.O.-driven auxiliary pump for tractors with insufficient oil capacity. Hydraulic lowering control possible.

Drawbar with mechanical suspension and heightadjustment (2 positions).





Models 9/11/15: Y-shaped drawbar with fastening as close as possible to the axles to provide a natural traction line and reduce the power requirements.



Trans-KTP 24/54

EXCEPTIONAL CONDITIONS!

Offer limited to 100 Trans-KTP 24/54 tipping trailers (ADTK2454/4-24).

EQUIPMENT INCLUDED

- Compact for a long body
- Closed tubular chassis
- Hydropneumatic drawbar with nitrogen accumulators for suspension when vehicle loaded and unloaded
- Integrated Ø 80 mm 4 t ball-joint towing eye
- Hydraulic skid, fully retractable in the drawbar
- · Rocker beam running gear
- BPW axles with 150 x 150 mm square
- Wheels 650/55R26.5 Vredestein Ø 1,400 x 650 mm, Endurion Trailer profile (special for civil engineering)

- Galvanised special steel mudguards
- Hydraulic bumper retracting automatically before the door opens
- Tapered body fully made of HARDOX 450 (thickness: 6 mm) including rear door: the best quality for civil engineering
- Tipping cylinder on double-oscillation frame, first 2 elements nitrided
- **Body protection: automatic shot blasting** + 2 coats of paint + baking
- Large 90° door opening (1.6 m above the body)
- Front extension (height: 45 cm)
- Front ladder
- Rigid hydraulic pipes for better protection and finish
- LED lights
- Individualised spare parts book

24/54: EXCEPTIONAL PRICE

Offer limited to 100 tipping trailers.

> ARDOX 450 JOSKIN The best in civil engineering

Trans-KTP24:54

Variety of extensions available on the whole **KTP** range

www.joskin.com 📵 😝 🖸 🕢

JOSKIN<mark>.</mark>

www.joskin.com



CONSTRUCTION TIPPING TRAILER ACTION

EXCEPTION

EXCEPTION

OFF-SEASON CONDITIONS

ON THE ENTIRE TRANS-KTP RANGE

Offer valid until 31.08.2025.



HARDOX 450

COMPLETE PRODUCT RANGE

JOSKIN heavy-duty tipping trailers are made from **HARDOX 450**, which has a tensile strength 4 to 5 times that of conventional steel. **Result: a very attractive quality/weight ratio and a higher payload!**







Rue de Wergifosse, 39 - 4630 Soumagne (Belgium) E-mail: info@joskin.com • Tel.: +32 (0)4 377 35 45

Scan the QR code to find out more about JOSKIN and discover the full range!

